



Mini IP Pan & Tilt Camera's Configuration Via Wi-Fi:

1. Connect your phone to your Wi-Fi then download the "yoosee" app from your mobiles app store
2. Open the application and create an account
3. Press the "+" symbol on the right side then select "Smartlink"
4. Plug the power supply into the camera, wait to hear beeping from the camera (if this does not happen reset the camera and wait for a minute)
5. Click "Next" then input your Wi-Fi password
6. Once the camera is found the beeping will stop
7. You will be prompted to input the cameras password (Default password is: 123)
8. Press "Save" (on the right hand side)
9. Click on the blue play button to see your cameras live picture.

Ethernet Connection Apply This Method If Wi-Fi Is Not Successful:

1. Connect the camera to the power supply and to your router with an Ethernet cable
2. Download the "yoosee" app from your mobiles app store
3. Open the application and create an account
4. Press the "+" symbol on the right side then select "Manual Add"
5. Enter the cameras ID (available on the camera's attached label)
6. Create a name for the camera
7. Enter the password (Default password is: 123)
8. If you wish to connect the camera to Wi-Fi then tap on the right side of the cameras name
9. Select Settings > Network Settings
10. Select your Wi-Fi broadcast from the list
11. You will be warned that you are changing networks select "Change"
12. Input your Wi-Fi password then press "OK"
13. Wait for 10 Seconds
14. Go back by pressing the arrow on the top left twice
15. Disconnect the Ethernet cable from your camera while the camera is still connected to Wi-Fi
16. Click on the blue play button to see your cameras live picture

Free App
yoosee