

SERAGE

QUALITY RELIABILITY VISION



5MP SPEED DOME PTZ



WHERE

Great Solution for auto tracking individuals and vehicle where 360 degree coverage is needed with pan tilt and zoom capability for around 75 meters with colour under low light at night and up to 100m Infra red range in complete darkness

WHY

Suitable for Car Parks , factories and any large space applications where 360 degree and close up monitoring and views is needed

SRSP5M33

Image Sensor	1/2.7" Progressive Scan CMOS
Max. Resolution	2592x1944
Min. Illumination	Color: 0.003 Lux @ (F1.6, AGC ON), B/W:0 Lux with IR 1/5 s to 1/20000 s
Shutter Speed	Yes
Slow Shutter	IR cut filter
Day & Night	33x optical
Zoom	
Focal Length	4.3mm to 142mm
FOV	Horizontal field of view: 55° to 2.3° (wide-tele), Vertical field of view: 41.6° to 1.7° (wide-tele), Diagonal field of view: 67.9° to 2.8° (wide-tele)
Aperture	Max. F1.6
Focus	Auto, manual
Supplement Light Range	IR Distance: up to 150 m
Supplement Light Type	IR
Movement Range(Pan)	360°
Movement Range(Tilt)	-10° to 90° (auto flip)
Pan Speed	Configurable from 0.6° to 200°/s; preset speed: 200°/s
Tilt Speed	Configurable from 0.6° to 90°/s, preset speed 100°/s
Proportional Pan	Yes
Presets	255
Patrol Scan	1 Scan
Pattern Scan	4 pattern
Power-Off Memory	Yes
3D Positioning	Yes
Main Stream	50 Hz: 20fps(2592x1944), 25 fps (2592x1520/2048x1536/2304x1296/1920x1080 1280x960/1280x720); 60 Hz: 20fps(2592x1944), 30 fps (2592x1520/2048x1536/2304x1296/1920x1080 1280x960/1280x720);
Sub-Stream	1280x960/1280x720); 50 Hz: 25 fps (1280x720/640x480/320x240); 60 Hz: 30 fps (1280x720/640x480/320x240); 50 Hz: 25 fps (640x480/320x240); 60 Hz: 30 fps (640x480/320x240)
Third Stream	
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265+/H.265/H.264+/H.264/MJPEG Third stream: H.265+/H.265/H.264+/H.264 8 kbps to 8192 kbps
Video Bit Rate	
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Audio Compression	G.711a/G.711u
Protocols	IPv4/IPv6, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DNS, DDNS NTP, RTSP, RTP, TCP/IP, UDP, DHCP, PPPoE Onvif (Profile S, Profile G, Profile T),Http API
API	Live View Up to 15 channels
Simultaneous User/Host	5 User
Security	Password protection, complicated password HTTPS encryption, IP address filter, control timeout settings
Client	VMS
Web Browser	IE11, Chrome 57+, Firefox 52+, Safari 11+
Day/Night Switch	Day, Night, Auto, Schedule
Image Enhancement	BLC, HLC, 3D DNR
Wide Dynamic Range (WDR)	120 dB
Defog	Digital defog
Image Stabilization	NA
Image Settings	Saturation, brightness, contrast, sharpness, Hue and white balance adjustable by client software or web browser
Privacy	4 privacy masks
Ethernet Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/SDHC/SDXC card up to 256 GB
Alarm	1 inputs, 1 output
Audio	1 inputs, 1 output
Reset	NA
Built-In Speaker	NA
Basic Event	Motion detection, alarm input and output
Deep Learning Function	Face Recognition, Human & Vehicle Detection Perimeter Intrusion Detection, Line Crossing Detection Stationary Object Detection, Crossing Counting, Heat Map
Smart Tracking	Auto-tracking
Alarm Linkage	Upload to FTP, send email, trigger alarm output trigger recording
Power	DC 12V/POE+, max. 25.6 W
Operating Condition	-30 °C to 60 °C (-22 °F to 149 °F). Humidity 90% or less (non-condensing)
Material	Metal
Dimension	Ø 206.4 mm × 351.8 mm (Ø 8.13" × 13.85") Approx. 3.7 kg (8.15lb.)
Protection	IP66