

## MAIN FEATURES



4 CH H.264



Support TVI/AHD/CVI/Analogue  
+ 2 IP - Total of 6 Cameras



4 Audio Input, 1 Output



2MP 1080p



Synchronous Playback 4CH



VGA and HDMI



USB 2.0 x 2



x1HDD up to 6TB



MODEL		SR2004D
Video Compression		H.264
Video System		NTSC/PAL
Operation System		Linux (Embedded)
Analog Video-Input /Output		4CH Inputs / VGA and HDMI Output
IP Video Input		2CH (Only IP up to 6CH)
Composite Video Input		Up to 6ch (Analog video + IP video)
Audio Input /Output		4CH Inputs /1CH Output (RCA)
Display	Resolution	Analog: 3MP (15fps), 1080p/720p, 960H IP: 4MP/3MP, 1080p/720p, 960H
	Feature	1/4/6/S.E.Q.
Record	Resolution	Analog: 3MP, 1080p/720p, 960H IP: 4MP/3MP, 1080p/720p, 960H
	Speed	Analog: 3MP: 5fps (Each CH) 1080p: PAL: 14fps (Each CH) 720p: PAL: 25fps (Each CH)/NTSC: 30fps (Each CH) 960H: PAL: 25fps (Each CH)/NTSC: 30ps (Each CH) IP: PAL: 25fps (Each CH)/NTSC: 30fps (Each CH)
IP-Recording Bandwidth (Maximum Input Bandwidth)		8Mbps ~24Mbps (Default is 8Mbps, decrease one analog channel can increase 4Mbps)
Maximum Output Brandwidth		32Mbps
Maximum Decode Performance		1080p: 2CH realtime
Recording Mode		Continuous/Manual/Motion detect
Synchronous Playback		4CH
Network Type		LAN, DHCP and DDNS
HDD Interface		1SATA HDD, up to 6TB
Multiplex Operation		Live display, record, playback, backup and network
USB		2xUSB (For mouse and backup/upgrade)
Sensor & Alarm I/O		4 CH Inputs /1CH Output
PTZ Control		Yes (RS485)
Mobile Surveillance		Support mobile phones based on iPhone and Android operation system
VGA/HDMI		1024x768, 1280x1024, 1440x900, 1920x1080
Power Supply		DC 12V/2A
Dimension (WxDxH)		300x227x53mm
Working Temperature		-10°C~+55°C
Working Humidity		10%~90%

\* Specifications subject to change without further notice

