




MAIN FEATURES


 **32 CH Built-in PoE**


 Recording Quality up to 4K

 2 Way Audio

 320Mbps Incoming Bandwidth

 Simultaneous VGA & HDMI outputs

 16 Alarm in / 4 Alarm out
4 Alarm input / 1 Alarm output

 Video Compression
H.265 / H.264

 USB 3.0 x 1, USB 2.0 x 2

 x 8HDD up to 48TB

MODEL	SR8032N
PoE	32 PoE
Video System	50Hz/60Hz
IP Video Input	32 Inputs
Video Output	1 VGA (up to 1080P) and 1 HDMI (up to 4K) output
Two-way Audio Line-in	1 Input, RCA (2.0 Vp-p, 1kΩ)
Audio Output	1 Output, RCA (2.0 Vp-p, 1kΩ)
Video Format	H.265/H.264
Max. Input Bandwidth	320Mbps
Display Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160 (4K)
Recording Resolution	8MP / 5MP / 4MP / 3MP / 2MP(1080P) / 1.3MP(960P) / 1MP(720P)
Peak Decode Performance	4 Channel real-time @ 4K 8 Channels real-time @5/4MP 16 Channels real-time @ 3MP 20 Channels real-time @ 2MP/1MP 4K mainstream 1ch, substream 32ch
Recording Mode	Continuous / Manual / Schedule / Motion detection / Sensor Triggered
HDD Supported	8 SATA HDD, up to 48TB
Network Interface	RJ-45 10/100Mbps self-adaptive Ethernet interfaces
Network Type	Static IP, DHCP, PPPoE
Onvif Support	Yes, Ver2.6.1
P2P Support	Yes, scan QR code to connect to NVR via mobile app
DDNS Support	Yes
UPnP Support	Yes, support to forward network port automatically
Cloud Storage Support	Yes, support to save pictures to Dropbox storage
CMS Support	Yes, No limitation on adding devices, max. 128 channels live view
Mobile App Support	iOS & Android APP: RxCamView, support to live view max. 80 channels simultaneously
Local Playback	Max. 16 Channels
Network Remote Playback	Max. 4 Channels Simultaneously via CMS, IE/Mac Safari or Mobile App
Playback Search	Date & Time / Event List / Smart Search
Playback Mode	Play, Fast Forward (max. 16x), Fast Rewind (max. 16x), Zoom
Backup Method	E-Sata, USB, Network
USB	USB 3.0 x1, USB 2.0 x2
e-SATA	Yes, 1 e-SATA port
PTZ Control	Yes, built-in RS485
Sensor & Alarm Port	16 inputs / 1 output
Keyboard Port	N/A
Power Supply	AC 100~240V, PoE Switch: 48V
Dimension(WxDxH)	440x460x89mm
Working Environment	-10°C~+55°C / 10%~90%RH
Working Environment	-10°C~+55°C / 10%~90%RH

* Specifications subject to change without further notice