

### MAIN FEATURES



**4MP**



2560 (H) × 1440 (V)



2.8-12mm Motorised Vari-Focal Auto Focus Lens



**40m** IR Distance







WDR 90dB



IP66



12v DC



MODEL	SRDN4VFW
Image Sensor	Sensor OV4689, 1/3" Progressive CMOS
Resolution	4MP 2560(H)×1440(V)
Min. Illumination	Color 0.1lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.8 ~ 12 mm (Motorised) H.FOV: 104 ~ 31°
F No.	F 1.6 ~ 2.9 ±5%
Day & Night	IR cut filter with auto switch
WDR	90dB
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	YES
Frame Rate	<b>Mainstream (1-20fps optional):</b> 4MP (2592x1520) 3MP(2048x1536)(2304x1296), 1080P (1920x1080), 960P(1280x960), 720P(1280x720) <b>Substream:</b> 720P (1280x720), VGA(640x480), QVGA(320x240) <b>Mobilestream:</b> VGA (640x480), QVGA (320x240)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection.
Protocols	TCP/IP, HTTP, DHCP,DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF( Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	40pcs (SMD)
IR Range	Up to 40m
SD storage	YES
Alarm Trigger	YES
Audio	YES
Video Output	YES
PoE	YES
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 7W
Dimension	Ø113 X 151mm
Weight	appr. 720g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C
Consumption	≤ 7W