

Night Light

MAIN FEATURES



5MP



2592 (H) × 1944 (V)



30m IR Viewable Length



2.8 mm Fixed Lens



0.05lux@F1.2(AGC ON),0Lux with IR ON



Digital WDR



IP66





12v DC/PoE



Built-in Audio & SD card

MODEL	SRDN5FW
Image Sensor	Sensor SC5235, 1/2.7" Progressive CMOS
Resolution	5MP 2592(H)×1944(V)
Scanning System	Progressive CMOS
Minimum Illumination	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ratio	F No.1.6±10%
Angular Field of View	Horizontal: 99°, Vertical: 72°, Diagonal: 131°
Min. Object Distance	0.2M
Lens Type	Fixed(M12)
Operational	
IR Viewable Length	Up to 30m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch Day/Night/Auto/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual/Indoor
Electronic Shutter Speed	1/5 ~ 1/20000s
Flip / Mirror	Flip/Rotation
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	Built-in microphone
Hardware Reset	Yes
Smart Feature	SMD
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264



ACCESSORIES



SRJ3/W



SRWI/W

Night Light



MODEL	SRDN5FW
Resolution	Mainstream 5MP(2592x1944),4MP(2592x1520) 3MP(2304x1296),1080P(1920x1080) ,720P(1280x720) Substream 720P(1280x720),VGA(640x480),QVGA(320x240)
Max. Framerate	50Hz: 15fps@5MP,25fps@4MP, 25fps@3MP/2MP/960P/720P 60Hz: 15fps@5MP,25fps@4MP, 30fps@3MP/2MP/960P/720P
Video Quality Ajustment	8Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream(Main/Sub)
IP	IPV4
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Max. User Access	Max 7 (admin+user)
Application Programming Inter- face	ONVIF(Profile S/G/T)
Web Viewer	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower
Operating Conditions	-30~+55°C/less than ≤ 95% RH
Storage Conditions	-30~+60°C/less than ≤ 95% RH
Ingress Protection	IP66
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Mechanical	
Color / Material	White/Metal
Dimension (WxHxD)	Ø71x151mm