

MAIN FEATURES



5MP 2160 (H) x 2160 (V)



1.1mm ,Angle of view: 360°



**Color 0.1lux @ F1.2(AGC ON) ;
B/W 0 lux @ IR ON**



Up to 5m IR Distance



IP64



12v DC/ PoE

MODEL	SRFN5UFO
Image Sensor	IMX326, 1/2.9" Progressive CMOS
Resolution	5MP 2160(H)x2160(V)
Shutter	1/5 ~ 1/20000s
Lens	1.1mm ,Angle of view: 360°
F No.	F 2.0 ±5%
Day & Night	IR cut filter with auto switch
Minimum Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
WDR	Digital WDR
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	yes
Frame Rate	Mainstream: 5MP (2160x2160), 1520x1520, 1080x1080, 720x720 Substeam: 720x720,480x480,240x240 Mobilestream: 480x480, 240x240
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	NA
Video Analytics	N/A
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMT- P,NTP,UPnP,SNMP,HTTPS,FTP,
System Compatibility	ONVIF(Ver 2.6)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	3pcs(SMD)
IR Range	Up to 5m
SD storage	Yes
Alarm Trigger	Yes
Audio	Yes
Video Output:	Yes
Reset Button	Yes
PoE	Yes
Water Proof	IP64
Power Supply	DC 12V/POE
Consumption	≤ 5W
Dimension	Ø120*55mm
Weight	appr 400g
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C